

MATERIAL SAFETY DATA SHEET

Original Revision Nov 14, 2007 by Great Meadow Correctional Facility, Division of Industries, PO Box 51, Comstock, NY 12821

SECTION 1: CHEMICAL PRODUCT AND COMPANY INFORMATION

PRODUCT NAME: CORCRAFT GREEN LINE FLOOR WAX REMOVER

MANUFACTURER: CORCRAFT - NEW YORK STATE DEPARTMENT OF CORRECTIONAL SERVICES
Great Meadow Correctional Facility, Division of Industries
PO Box 51
Comstock, NY 12821

TELEPHONE: 888 - 697 - 6233

PRODUCT NUMBERS: U01GRWRA0 - 6/1 Gallon Bottle
U01GRWRB0 - 5 Gallon Pail
U01GRWRC0 - 55 Gallon Drum
U01GRWRD0 - 4/1 Gallon Bottle

HMIS RATING **H = 2** **F = 0** **R = 0**

The HMIS (Hazardous Materials Identification System) is a subjective rating system developed by the National Paint and Coating Association. Numerical ratings for health (H), flammability (F), and reactivity (R) are made using a scale of 0-4 where 0= no hazard, 1 = slight hazard, 2 = moderate hazard, 3 = high hazard and 4 = extreme hazard.

SECTION 2: HAZARDOUS INGREDIENTS/IDENTITY INFORMATION

HAZARDOUS COMPONENT	PERCENT	CAS #	ACGIH TLV-TWA	OTHER LIMITS RECOMMENDED
Monoethanolamine	5 - 10	141 - 43 - 5	3 ppm	6 ppm STEL
Dipropylene Glycol n-Butyl Ether	5 - 10	29911-28-2	NE	NE
Isopropyl Alcohol	< 1	67 - 63 - 0	400 ppm	500 ppm STEL

SECTION 313 SUPPLIER NOTIFICATION

The toxic chemicals noted above which are marked with an (*) are subject to the reporting requirements of Section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 and of 40 CFR 372. Not all chemicals subject to Section 313 of EPCRA appear on the OSHA Floor List of Chemicals.

SECTION 3: HAZARDS IDENTIFICATION

EYES: Direct contact may cause eye irritation.

SKIN: Prolonged or repeated contact may cause irritation.

INHALATION: Excessive exposure may cause respiratory irritation.

INGESTION: May cause gastrointestinal and irritation of the mouth or throat.

SIGNS AND SYMPTOMS OF EXPOSURE: Eye contact will cause irritation, seen as redness and swelling. Prolonged skin contact will cause irritation seen as redness. Ingestion may cause pain or discomfort in the mouth, throat or stomach.

SECTION 4: FIRST AID MEASURES

EYES: If exposed, flush with large amounts of water for 15 minutes and get medical attention if irritation persists.

SKIN: Wash with plenty of clear water. Seek medical attention if irritation develops.

INHALATION: Get fresh air if exposed and seek medical attention if condition does not improve.

INGESTION: If swallowed do not induce vomiting. Drink two glasses of water and seek medical attention immediately.

SECTION 5: FIRE FIGHTING METHODS

Corcraft GREEN LINE Floor Wax Remover is a water-based alkaline liquid. Use foam, dry chemical, carbon dioxide or water spray for fires involving this product. Firefighters should wear self contained breathing apparatus with full face masks.

SECTION 6: ACCIDENTAL RELEASE MEASURES

MATERIAL SAFETY DATA SHEET

Absorb and collect excess product and containerize for reuse. For product that cannot be reused and must be disposed of, appropriate disposal methods should be followed. Corcraft GREEN LINE Floor Wax Remover's management and disposal should follow State/Federal guidelines for release reporting.

SECTION 7: HANDLING AND STORAGE

Corcraft Floor Wax Remover may irritate eyes and skin and handling procedures should avoid direct skin or eye contact. When diluting this product, do so in a well ventilated area. This product should be stored in the original containers in a cool and dry location. Store between 40° - 120° F. Keep from freezing.

SECTION 8: EXPOSURE CONTROLS, PERSONAL PROTECTION

Ventilation:	Normally Sufficient
Respiratory Protection:	Not normally Required. Avoid breathing vapors of concentrate. If vapors may exceed the PEL, use NIOSH/OSHA approved respirator.
Skin:	Wear protective gloves if any contact with the product is possible.
Eyes:	Protective goggles or face shield should be worn when pouring or mixing product to avoid any face or eye contact.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Flash Point:	None to boiling
Water Solubility:	Complete @ 1:4 dilution
Vapor Pressure:	Unknown
Specific Gravity	1.001
Boiling Point	Unknown
Appearance / Odor	Low viscosity liquid with mild odor

SECTION 10: STABILITY AND REACTIVITY

Corcraft Floor Wax Remover is a non-reactive, stable water based liquid. However, as with any cleaning product, mixtures with other products should be avoided. Corcraft Floor Wax Remover is an alkaline liquid and contact with strong acids should be avoided.

SECTION 11: TOXICOLOGICAL AND ECOLOGICAL INFORMATION

Corcraft Floor Wax Remover is not known to be a carcinogen or toxic. Over exposure to this product may produce the conditions listed in Section 3. Releases to the environment do require release response, notification and reporting requirements for ignitable wastes.

SECTION 12: TRANSPORTATION AND DISPOSAL

Monoethanolamine and Ethylene glycol are reported in EPA TSCA Inventory.
Isopropanol is reported in the EPA TSCA Inventory and the EPA Genetic Toxicology Program.

SECTION 13: REGULATORY INFORMATION

Releases to the environment in full-strength will require immediate containment and collection, as well as emergency reporting/notification depending on the user's State requirements.

The information and recommendations contained herein are based upon data believed
To be correct. However, no guarantee or warranty of any kind expressed or implied